



Traders Warehouse
Security Distribution Group UK

EAT•N

Powering Business Worldwide

Keep connected
24/7 anytime,
anywhere!



PRODUCT CATALOGUE 2018



traderswarehouse.co.uk

National Telephone Number: **0330 122 2408**

Birmingham
0330 122 2409

Derby
0330 122 2405

Glasgow
0330 122 2403

Milton Keynes
0330 122 2406

Preston
0330 122 2402

Page No.	Content
03	SecureConnect enabled Control Panels
04	Scantronic Control Panels
05	i-on Control Panels range
06	Keypads
07	Camera's
08-09	Detector's
10	Sounders
11-12	Communicators
13	Relay Cards
14	Transmitters and Receivers
15	Expanders
16-17	Kits
18	Installation Accessories
19	Notes

MPN / QFC	Description	Grade
CONTROL PANEL		
i-on Compact 104.991	The i-on compact includes 20 radio zones, 40 years of class leading scantronic radio, Built in Communications (SIA IP ARC) as standard, Plug on GSM or PSTN module for dual-path communications, Built in Ethernet port, Wi-Fi module adaptability, Compatible with Eaton's range of radio peripherals and Easy maintenance with hinged access. Available in kit format.	Grade 2
i-on30R 104.131	The i-on30R includes 30 zones on-board expandable to 60, Hybrid expansion using EXP-R10 / R30 / W10 / PSU, Ethernet / web server / virtual keypad, Visual verification, Perimeter zone functionality, SMS control, Plug on ARC / Speech / SMS for PSTN / GSM, Class leading Scantronic radio and UDL / ARD over IP or PSTN	Grade 2
i-on40H 104.132	This i-on40H includes 30 radio and 10 wired zones expandable to 80, Hybrid expansion using EXP-R10/R30/ W10/ PSU, Ethernet/ web server/ virtual keypad, Visual verification, Perimeter zone functionality, SMS control, Plug on ARC/ Speech/ SMS for PSTN/ GSM, Class leading Scantronic radio and UDL/ ARD over IP or PSTN	Grade 2
i-on Style 104.973	The i-on Style includes 40 radio zones with additional 4 wired zones, 30 radio outputs, High performance Scantronic radio, 4 wired outputs - 2 x transistor 2 x relay, Ethernet/ Web server/ Virtual Keypad, Plug on GSM module to give tri-path communications, SIA/IP ARC communications, Email notifications, SMS control, Visual verification via internal and external IP cameras, External perimeter zone functionality, Social care features, Built in speech dialer and Field-proven reliability of the Scantronic i-on range	Grade 2
WiFi Adapter 104.983	The I-WiFi01 provides wireless network connectivity, compatible with Generation 2 panels, connected, powered and installed internally and converts wired Ethernet into a wireless signal.	-



i-on Compact



i-on30R



i-on40H



i-on Style



I-WiFi01

MPN / QFC	Description	Grade
SCANTRONIC CONTROL PANELS		
9651PD-41 104.516 9651PD-43 104.922	<p>The Scantronic 9651 is a Grade 2X fully programmable eight zone control panel, with full and part-set options.</p> <p>Up to four keypads can be added to the system, allowing easy operation from any location.</p> <p>When using a 9943 keypad, the 9651 can be easily set and unset using a proximity tag without the need to remember the access code.</p>	Grade 2



9651PD-41
&
9651PD-43

MPN / QFC	Description	Grade
CONTROL PANEL		
i-on30EXDKP 104.131	The i-on30EXDKP includes 10 FSL zones on board, expandable to 30, Supports downloader, On-board communicator, One transistor output, 12 digital plug-by outputs, Supports up to 7 Ah battery, Sold with the KEY-KP01	Grade 2
i-on50EXDKP 104.099	THE i-on50EXDKP includes 10 FSL zones on board, expandable to 50, Includes web server and supports downloader, On-board communicator, Three panel outputs, including one single clean contact relay on board, 16 digital plug-by outputs, Supports up to 17 Ah battery, Sold with the KEY-KP01.	Grade 2
i-on160EXKP 104.937	The i-on160EXKP includes Built-in web server, Maximum zones 160 (10 wired 150 hybrid), Users 500, Maximum bus devices 45, Plug by outputs 16, Total number of log events 2000, Digi-modem Plug-on (i-dig02, i-sd02 or i-gsm02), Setting options Part set (3) or partitions (20, Power supply 3 Amp and Local port USB, Sold with the KEY-KP01.	Grade 2 or 3
i-on1000EXKP 104.980	The i-on1000EXKP includes 10km spread over 10 buses using standard alarm cable with high tolerance for daisy chain or star comfy durations, 250 bus devices (25 per bus), 1000 zones and users, 1000 outputs (wired or radio), Push button addressing, 50 partitions/wards, 5000 mandatory log events, Sold with the KEY-KP01.	Grade 2 or 3
Menvier 30KPZ 104.921	The Menvier 30 includes Compact control panel, ARD (automatic remote diagnostics) fully supports remote servicing, Upload/ Download compatible, Ten FSL zones, expandable to 30 zone, Speech dialer plug-on option, Two custom outputs and One shunt group	Grade 2
Menvier 40KPZ 104.919	The Menvier 40 includes part set and ward mode, Includes web server and supports downloader, Built-in USB port for onsite software upgrades, Supports full range of i-on communicators, Support for downloader over USB, PSTN and IP, 16 plug-by outputs, 5 custom outputs, 1 shunt groups and Sold with KEY-KP01	Grade 2 or 3
Menvier 100KPZ 104.481	The Menvier 40 includes BS8243 compliant, Built-in web server, Maximum zones 100 (10 wired 90 hybrid, Users 250, Maximum bus devices 45, Plug-by outputs 16, Total number of log events 1,250, Digi modem built-in, Setting options Part set (3) or wards (10), Power supply 1.5 Amp and Local port USB	Grade 2 or 3
Menvier1000KPZ 104.972	The Menvier1000 includes 10km spread over 10 buses using standard alarm cable with high tolerance for daisy chain or star comfy durations, 250 bus devices (25 per bus), 1000 zones and users, 1000 outputs (wired or radio), Push button addressing, 50 partitions/wards, 5000 mandatory log events, 50 custom outputs (Menvier1000 only)and 25 shunt groups (Menvier 1000 only)	Grade 2 or 3



i-on30EXDKP
&
i-on50EXDKP
&
i-on160EXKP
&
i-on1000EXKP



Menvier 30KPZ
&
Menvier 40KPZ
&
Menvier 100KPZ
&
Menvier 1000KPZ

MPN / QFC	Description	Grade
KEYPADS		
KEY-RKPZ 104.962	The two-way KEY-RKPZ keypad offers the user full access to configure, set or unset the system. At the same time, it allows you – and your customer – welcome flexibility when it comes to choosing the optimum location. Linked wirelessly to its own base station which talks to the control unit via a standard RS485 wired connection.	Grade 2 and 3
KEY-K01 104.931	KEY-K01 - A keypad which includes: <ul style="list-style-type: none"> • Navigation key for easy access to the user and installer menus • Status LED that can be turned on or off from within the keypad menu 	Grade 2 and 3
KEY-KP01 104.927	KEY-KP01- A keypad which includes: <ul style="list-style-type: none"> • Navigation key for easy access to the user and installer menus • Status LED that can be turned on or off from within the keypad menu • Internal prox reader connections for an external prox reader (KEY-EP) 	Grade 2 and 3
KEY-KPZ01 104.998	KEY-KPZ01 - A keypad which includes: <ul style="list-style-type: none"> • Navigation key for easy access to the user and installer menus • Status LED that can be turned on or off from within the keypad menu • Internal prox reader connections for an external prox reader (KEY-EP) • Connections for two zones and a programmable output 	Grade 2 and 3
I-KP01 104.058	The i-KP01 is a wired keypad with large LCD display and built-in dedicated, compliant HUA function. Navigation and text input is a similar user experience to mobile phones, enabling the installer and user to scroll through easy to follow menus.	Grade 2 and 3
I-RK01 104.063	The i-RK01, is a radio keypad powered by three alkaline AA batteries with a built-in dedicated, compliant HUA function. Alternatively it can be attached to an external DC power supply.	Grade 2
KEY-FKPZ 104.949	The KEY-FKPZ range is designed to fit a single gang back box for a simpler and neater installation. They offer the dependable, easy-to-use functionality you and your customers expect from Eaton Security including full operability with Scantronic and Menvier panels via i-on style controls (version 4.04 and higher).	Grade 2 and 3



KEY-RKPZ
&
KEY-K01
&
KEY-KP01
&
KEY KPZ01
&
KEY-FKPZ



I-KP01



I-RK01



KEY-FKPZ

MPN / QFC	Description	Grade
CAMERA'S		
CAM-INT-00 903.208	High definition 1080P camera, Built-in web server for straightforward configuration, Wi-Fi or wired Ethernet connectivity, Power over Ethernet or local Power Supply Unit, Night IR up to 8 meters, 15 images provided: 5 seconds pre and 10 seconds post event, Firmware upgradeable, Compatible with the next generation of i-on (Software version 5 and higher) and WPS Enabled	-
CAM-EXT-00 903.209	High definition 1080P camera, Built-in web server for straightforward configuration, Weatherproof IP66 rated for outdoor use, Wi-Fi or wired Ethernet connectivity, Power over Ethernet or local Power Supply Unit, Night IR up to 20 meters, 3 Axis mounting bracket, 15 images provided: 5 seconds pre and 10 seconds post event, Firmware upgradeable, and Compatible with the next generation of i-on (Software version 5 and higher)	-



CAM-INT-00




CAM-EXT-00

MPN / QFC	Description	Grade
DETECTOR'S		
DET-REXT-PIR30 104.984	Low maintenance covert detection <ul style="list-style-type: none"> • Creep mirror detects activity immediately below the unit <ul style="list-style-type: none"> • Detection range up to 30m • 500m radio range in free space on 868MHz <ul style="list-style-type: none"> • IP 65 Protection rating • Typical battery life 2 years (based on 200 activations per day) <ul style="list-style-type: none"> • 2 x 3V CR123 batteries • Compatible with full i-on & New Menvier ranges 	Grade 2
DET-REXT-IR50/100 104.996	Low maintenance covert detection <ul style="list-style-type: none"> • Creep mirror detects activity immediately below the unit <ul style="list-style-type: none"> • Detection range up to 30m • 500m radio range in free space on 868MHz <ul style="list-style-type: none"> • IP 65 Protection rating • Typical battery life 2 years (based on 200 activations per day) <ul style="list-style-type: none"> • 2 x 3V CR123 batteries • Compatible with full i-on & New Menvier ranges 	Grade 2
DET-RDC-W_B_G White 104.988 Brown 104.989 Grey 104.990	A wireless slimline door contact for detecting threats and alerting system users. Keeping property, people and belongings safe. With a choice of 3 different finishes to suit all installations.	Grade 2
734 104.446	Radio door contact with configurable second radio channel. For use with HUA (PA), door contact, key switch or other voltage free device. Compact unit with replaceable CR2 lithium battery.	Grade 2
738 104.413	Compact radio shock detector using proven, configurable and patented sensing technology. For door and window installations, it's available in a white or brown housing. The DET-RDCS has dual functionality as both shock detector and magnetic contact.	Grade 2



DET-REXT-PIR30



DET-REXT-IR50/100



DET-RDC-W_B_G



734



738

MPN / QFC	Description	Grade
DETECTOR'S		
739 104.415	Radio break glass detector designed with proven, pattern recognition technology. Suitable for use in quiet environments for 360 degree acoustic detection. Lithium i-on battery, 868mhz frequency, Range up to 6m	Grade 2
XCEL Series XCELR 104.214 XCELWPT 104.086 XCELRPT 104.070	The XCEL PIRs have a specially designed spherical lens that generates five layered beams, combined with a dual element sensor to deliver superior detection and catch performance. The PIRs are certified to all EN50131 standards, with the radio technology field proven over many years.	Grade 2
DET-RWATER 104.997	The fully supervised radio water detector, the DET-RWATER, will signal the control panel if presence of water at the specific location. A combination of radio functionality and a 1m cable to the detection head means true flexibility for most interior environments including basements or adjacent to washing machines.	-
DET-RARB 104.217	Radio Assistance Required Button signals the request for local assistance through the use of just a single button. Designed to be either wall or desk mounted, the DET-RARB can be learned to EXP-R10 and EXP-R30. The panels can be programmed to activate a range of outputs.	-
DET-RSMOKE 104.944	The DET-RSMOKE is an optical radio smoke detector designed to work with Eaton's Security business' range of radio and hybrid control panels. The device is compatible with i-on, new Menvier and our legacy 868 systems. Installers can utilise the full range of communications options across the panel ranges.	-
M12 104.909	The M12 is the fire detector for almost all conditions including rapid rises in temperature, slow burning and smouldering fires. The detector incorporates optical and heat detection technology as well as recognising and compensating for gradual build-up of dust.	-



739



XCEL Series



DET-RWATER



DET-RARB



DET-RSMOKE



M12

MPN / QFC	Description	Grade
SOUNDERS		
SDR-xEXT 104.130	<p>A capsule range of external sounders, in three colours, with options for wireless, wired and decoy. 3 colours: blue, amber and red.</p> <p>Designed for use with i-on and Menvier, new and legacy 868MHz systems. Wired variants also compatible with third-party control units.</p>	Grade 2 and 3
SDR-RINT 104.957	<p>The SDR-RINT includes a 2 way radio, Uses 4 x AA batteries, 80dB output, All system sounds including entry/exit, fault and alarm tones, Multiple internal radio sounders can be put on the same system, Compatible with all i-on and new Menvier control panels with v4.05 software or higher and if applicable, radio expander software v2.09 or higher</p>	Grade 2



SDR-xEXT



SDR-RINT

MPN / QFC	Description	Grade
COMMUNICATORS		
<p>i-SD01 104.067</p>	<p>Multi-function, plug-on communicators for the i-on and Menvier range. Providing ARC reporting, SMS and speech messages all over standard PSTN. ARC reporting supports multiple formats including; fast format, contactID, SIA levels 1, 2 and 3. SMS provides up to four contacts with a variety of status messages. The speech dialler allows personalised voice messages to be transmitted to up to four recipients.</p>	-
<p>i-SD02 104.084</p>	<p>The i-SD02 is part of a range of multi-function, plug-on communicators for the i-on and Menvier range. Providing ARC reporting, SMS and speech messages all over standard PSTN or GSM. ARC reporting supports multiple formats including; fast format, contactID, SIA levels 1, 2 and 3. SMS provides up to four contacts with a variety of status messages.</p>	-
<p>8400 104.092</p>	<p>The 8400 is a wired, auto-dialling digital communicator, capable of being programmed to support monitored installations that require a police response.</p>	-
<p>i-GSM02 104.082</p>	<p>The i-GSM02 is part of a range of multi-function, plug-on communicators for the i-on and Menvier range. Providing ARC reporting, SMS and speech messages all over standard PSTN or GSM. ARC reporting supports multiple formats including; fast format, contactID, SIA levels 1, 2 and 3. SMS provides up to four contacts with a variety of status messages</p>	-
<p>i-GSM03 870.014</p>	<p>The i-GSM03 is a plug-on GSM module for control units such as i-on Style to provide communicators over a GSM mobile phone network.</p>	-



i-SD001



i-SD002



8400UK-21



I-GSM02




I-GSM03

MPN / QFC	Description	Grade
COMMUNICATORS		
<p>SD1 104.109</p>	<p>Stand-alone speech dialler that can complement any system requiring alerts of changes in system conditions.</p> <p>All messages are sent over standard PSTN line, using personalised voice messages to be transmitted to up to four recipients. A complete unit, with keypad and display for programming and set up.</p>	-
<p>TSD2 104.110</p>	<p>The TSD2 also has built-in programmable outputs which can be operated remotely over PSTN. And its integrated microphone and speaker adds to the ability to listen in and speak to the site remotely. Both are complete units, with keypad and display for programming and set up</p>	-
<p>SD3 104.111</p>	<p>Stand-alone speech dialler that can complement any system requiring alerts of changes in system conditions, including temperature monitoring.</p> <p>All messages are sent over standard PSTN line or GSM, enabling SMS and speech messages. Personalised voice messages can be transmitted to up to ten recipients. A complete unit, with keypad and display for programming and set up.</p> <p>With built-in programmable outputs which can be operated remotely over PSTN or GSM. The built-in microphone and speaker adds to the ability to listen in and speak to the site remotely.</p>	-
<p>SD-GSM 104.072</p>	<p>Stand-alone speech dialler that can complement any system requiring alerts of changes in system conditions, including temperature monitoring. All messages are sent over GSM, enabling SMS and speech messages.</p> <p>Personalised voice messages can be transmitted to up to ten recipients. A complete unit, with keypad and display for programming and set up. With built-in programmable outputs which can be operated remotely over GSM.</p> <p>The integrated microphone and speaker adds to the ability to listen in and speak to the site remotely.</p>	



SD1
&
TSD2
&
SD3
&
SD-GSM

MPN / QFC	Description	Grade
RELAY CARDS		
8600 104.455	The 8600EUR-00 relay expansion card is designed to fit a range of Eaton security equipment converting transistorised inputs to clean contact relay inputs. This card contains eight relays, each with its own dedicated input.	-
i-RC01 104.076	The i-RC01 relay card is used with i-on16, i-on40, EXP-W10 and EXP-WCC to convert the four on board transistorised outputs to clean contact relays. The relay card uses screw-free mountings specifically designed into these products for this purpose.	-



8600



i-RC01

MPN / QFC	Description	Grade
TRANSMITTERS AND RECEIVERS		
701rEUR-50 104.429	These wearable devices are narrow band 868MHz radio transmitters and can be used to trigger outputs on any of the compatible receivers. The devices are powered by a non-replaceable lithium battery technology, which is designed to give typically three years of life if used twice per day.	Grade 2
702rEUR-00 104.431		
703rEUR-00 104.432	The 703 is a four channel radio transmitter that can be used in conjunction with any wired detector or device to provide a radio solution when wiring is not possible. Includes four wired inputs that can be connected to many building management systems (BMS) to indicate alarm sensor activation. Offering a variety applications by transmitting signals to any of our current radio receivers.	Grade 2
705rEUR-00 104.433	The range of transmitters have a double push radio channel for elective requests for assistance (HUA). Powered by lithium battery technology, for a longer working life cycle. The 705 gives you the flexibility of a secondary programmable channel whilst the 706 has a built-in tilt sensor for 'man down'. 710 is a single channel HUA radio device with belt/pendant mounting options and replaceable battery with extended radio range. The 726 a long range, single channel radio HUA device with belt clip.	Grade 2
706rEUR-00 104.434		
710rEUR-00 104.435		
726rEUR-50 104.442		
726rEUR-60 104.443		
762rEUR-00 104.458	This highly flexible range of receivers can be used as a stand-alone unit or linked to other systems to provide radio integration. Applications include signalling the opening or closing of doors or windows and the remotely switching of connected devices such as lights, doors and machines. Includes two relay outputs that can be connected to many building management systems (BMS) to indicate alarm sensor activation	Grade 2
768rEUR-50 104.459		
769rEUR-50 104.460		



701 & 702



705 & 706 & 710 & 726 & 726



762



768 & 769

MPN / QFC	Description	Grade
EXPANDERS		
<p>EXP-R10 104.074</p> <p>EXP-R30 104.085</p>	<p>The EXP-R10 and EXP-R30 are designed for Grade 2 installations, as part of PD6662:2010 these expanders can provide radio HUA functionality in Grade 3 installations. These radio expanders work with the latest i-onEX and Menvier intruder detection systems.</p> <p>Uniquely, the EXP-R10 and EXP-R30 provide radio outputs which can be used to trigger remote equipment for example gates at the end of a drive, or lights across yard or garden. Additionally these expanders support Radio Grid Roaming where expanders are combined to create a single, virtual radio grid. Allowing the transmissions of enabled devices to be processed regardless of their location within the grid's range.</p>	Grade 2
<p>EXP-PSU 104.100</p>	<p>The EXP-PSU, EXP-W10 and EXP-WCC are designed and approved to be used as part of a Security Grade 2 or 3 system. All remote intelligent expanders, they are intended to be used in wired alarm systems with i-onEX and current Menvier ranges of control panels at the heart of the system. Benefiting from full diagnostics and fault reporting via the bus. Increased installation flexibility; with ten zones on board and suitable for a range of FSL values, two wire CC and four wire CC compatibility.</p>	Grade 2 and 3
<p>EXP-W10 104.073</p>	<p>The EXP-PSU, EXP-W10 and EXP-WCC are designed and approved to be used as part of a Security Grade 2 or 3 system. All remote intelligent expanders, they are intended to be used in wired alarm systems with i-onEX and current Menvier ranges of control panels at the heart of the system. Benefiting from full diagnostics and fault reporting via the bus. Increased installation flexibility; with ten zones on board and suitable for a range of FSL values, two wire CC and four wire CC compatibility. Transistorised outputs provided as standard on EXP-W10 and EXP-WCC. Reduce maintenance times with the device locate feature using on board piezo sounders.</p>	Grade 2 and 3



EXP-R10 & EXP-R30



EXP-PSU



EXP-W10

MPN / QFC	Description	Grade
I-ON COMPACT KITS		
i-on Compact Audible Kit 104.992	This Eaton SecureConnect™ enabled - increase your revenue stream with 24/7 remote access to Cloud and customer App, Single box solution - reducing installation time, Low profile discreet design - provide your customers with a non-intrusive alarm system to fit in any location within their home, Future Flexible - as new features are introduced you can update the system remotely or locally, Field proven tried and tested i-on platform - giving you a common interface across the i-on family and a built in Ethernet IP - for flexible and secure communication options.	Grade 2
i-on Compact PSTN kit 104.987	Audible kit with PSTN Dialler Kit includes: 1 x COMPACT Panel 3 x XCELPRPT 1 x DET-RDC-W 1 x FOB-2W-4B 1 x SDR-REXT-BL-NC 1 x PSTN Dialler	Grade 2
i-on Compact WiFi kit 104.010	Audible kit with WiFi communicator Kit includes: 1 x COMPACT Panel 3 x XCELPRPT 1 x DET-RDC-W 1 x FOB-2W-4B 1 x SDR-REXT-BL-NC 1 x WIFI Communicator	Grade 2
i-on Compact GSM kit 104.993	Audible kit with GSM communicator Kit includes: 1 x COMPACT Panel 3 x XCELPRPT 1 x DET-RDC-W 1 x FOB-2W-4B 1 x SDR-REXT-BL-NC 1 x GSM communicator	Grade 2
i-on30RKIT-WKP 104.218	Kit contents: <ul style="list-style-type: none"> •i-on30R- 30 radio zone control panel •XCELPRPT x3- Internal pet tolerant PIRs •DET-RDC-W- Slimline door contact (white) <ul style="list-style-type: none"> •PROXTAGKP5- 5 Proximity tags •KEY-KPZ01- Wired keypad with built-in prox •SDR-REXT-BL-NC - External Sounder Blue 	Grade 2



i-on Compact Audible Kit



i-on Compact PSTN Kit



i-on Compact WiFi Kit



i-on Compact GSM Kit



i-on30RKIT-WKP

MPN / QFC	Description	Grade
I-ON COMPACTS KITS		
i-on30RKIT-WKP-BL 104.219	Kit contents: <ul style="list-style-type: none"> •i-on30R- 30 radio zone control panel •XCELRPT x3- Internal pet tolerant PIRs •DET-RDC-W- Slimline door contact (white) <ul style="list-style-type: none"> •PROXTAGKP5- 5 Proximity tags •KEY-KPZ01- Wired keypad with built-in prox •SDR-REXT-BL-NC - External Sounder Blue 	Grade 2
i-on30RKIT-RKP 104.019	Kit contents: <ul style="list-style-type: none"> •i-on30R- 30 radio zone control panel •KEY-RKPZ-KIT- Fully compatible with Scantronic i-on range and new Menvier panels •XCELRPT x3- Internal pet tolerant PIRs •DET-RDC-W- Slimline door contact (white) <ul style="list-style-type: none"> •PROXTAGKP5- 5 Proximity tags 	Grade 2
i-on30RKIT-RKP-BL 104.020	Kit contents: <ul style="list-style-type: none"> •i-on30R- 30 radio zone control panel •KEY-RKPZ-KIT- Fully compatible with Scantronic i-on range and new Menvier panels •XCELRPT x3- Internal pet tolerant PIRs •DET-RDC-W- Slimline door contact (white) <ul style="list-style-type: none"> •PROXTAGKP5- 5 Proximity tags •SDR-REXT-G2-BL-NC- Scantronic Radio External Sounder with Blue Lense is Designed for use with i-on and Menvier Radio alarm systems. 	Grade 2
i-on30RKIT-RKP-RD 104.023	Kit contents: <ul style="list-style-type: none"> •i-on30R- 30 radio zone control panel •KEY-RKPZ-KIT- Fully compatible with Scantronic i-on range and new Menvier panels •XCELRPT x3- Internal pet tolerant PIRs •DET-RDC-W- Slimline door contact (white) <ul style="list-style-type: none"> •PROXTAGKP5- 5 Proximity tags •SDR-REXT-G2-RD-NC- External Sounder Radio Red Lens White Cover 	Grade 2



i-on30RKIT-WKP-BL



i-on30RKIT-RKP



i-on30RKIT-RKP-BL



i-on30RKIT-RKP-RD

MPN / QFC	Description	Grade
INSTALLATION ACCESSORIES		
<p>DET-RSURV01 104.968</p>	<p>This simple to use radio site survey tool effectively identifies the best location for radio devices, enabling optimum radio performance by evaluating the radio signal strength before installation.</p> <p>Giving complete confidence in the correct positioning of your radio device by confirming the expected signal strengths.</p> <p>Eliminating potential challenges before they emerge by identifying potential unsuitable positions.</p> <p>The hand held device operates with a one-button push and the simple red/green indicator means training is not necessarily required. An additional numerical display within the receiver housing offers an accurate measure of radio signal strength, if required.</p> <p>Contained within a professional, protective case with optional space for other product demonstration and literature.</p>	-
<p>KEY-ENG 104.967</p>	<p>Portable, lightweight i-on keypad to assist in your installations. Easy to carry in a protective case with belt clip for quick access. Move engineering session around installation. Plugs on to i-onEX and new Menvier control panels and expanders. Cuts installation time. No need to locate the nearest keypad to make configuration changes or to carry out localised testing.</p>	-



DET-RSURV01



KEY-ENG

Derby Head Office: 0330 122 2405

Royal Scot Road
Pride Park
Derby DE24 8AJ

derby@traderswarehouse.co.uk

Glasgow: 0330 122 2403

Unit 6 Eglinton Trading Estate
22 Cumberland Street
Glasgow G5 9QJ

glasgow@traderswarehouse.co.uk

Birmingham: 0330 122 2409

Unit 52 Cuckoo Road Ind. Estate
Cuckoo Road
Birmingham B7 5SY

birmingham@traderswarehouse.co.uk

Milton Keynes: 0330 122 2406

Vermont Place
Tongwell
Milton Keynes MK15 8JA

miltonkeynes@traderswarehouse.co.uk

Preston: 0330 122 2402

Unit 23 Momentum Business Park
Nook Lane, Bamber Bridge
Preston PR5 6BD

preston@traderswarehouse.co.uk

For technical support call 0330 122 2410



www.traderswarehouse.co.uk

While we try to be as accurate as possible with specification, images and pricing, they are subject to change without notice
All prices in this booklet exclude VAT